

Magnum CSN14 Converter Switches Configuration Guide

1.) **Select your application environment:** a.) Office Grade (0° to +40°C), b.) Hardened/Factory Floor (-25° to +60°C), or c.) Premium/Outdoor Rated (-40° to +75°C).

All CSN14 Converter Switches have three ports—two 10/100 RJ-45 Copper and one 10 Mb fiber.

2.) **All fiber ports are 10Mb ports with ST-type fiber connectors**

Multi-mode fiber ports support 2km; Single-mode ports support 10km; for single mode, add an "S" in place of the asterick (*) in the chart below; when multi-mode is desired, leave the "S" out.



3.) **Select power type:** 12VDC, 24VDC, 48VDC, 115VAC(d), 230VAC(i)

Notes: a.) When ordering 24VDC hardened or premium models, an HR or PR version is available that includes the DIN-Rail bracket attached. b.) When ordering hardened or premium AC models, the external power supply has an -Hd or -Hi OR a -Pd or -Pi to designate the level of power supply hardening. These AC models include an external 12vdc terminal block in addition to the external AC power supply jack.

4.) **Examples:**

Factory hardened, panel mount CSN14 w/115 VAC power and a fiber ST port = **CSN14H-Hd**
 Premium rated CSN14 w/ a single-mode ST fiber port & 24VDC w/DIN-Rail bracket = **CSN14SPR-24VDC**
 Office grade, panel mount CSN14 w/ a multi-mode ST fiber port & 48VDC = **CSN14S-48VDC**

5.) **Mounting Hardware for Converter Switches (panel mount brackets are standard)**

DIN-RAIL-MC2 DIN-Rail mounting hardware for "14-series" CS14/CSN14 or MC or ES42/ESD42 Switches.

DUAL-SRC-24KIT Cable kit for 24VDC input to the DC power input jack of one CS14/CSN14, any 24VDC model

MC14-TRAY Rack-mount tray for "14-series" CS14/CSN14 or MC or ES42/ESD42 Switches, 2.25"H, up to 16 units mix-match

MC14-TR+PS9 Same as MC14-TRAY, but includes the 9vdc PS and ten connectors for CS14, CSN14, 14E, ES42/ESD42 types.

The power supply is auto-ranging 110-240vac, 50-60Hz, rated at 40 watts and 50°C.

MC14-TR+PS9X2 Same as MC14-TR+9PS, but with 2nd 9vdc PS and 2 groups of 8 connectors for 14-series, CS, and ES.

Model Number	Ambient Temp			Power Input						Mounting
	0° to +40° C	-25° to +60° C	-40° to +75° C	d,i AC external	Hd, Hi external +12V Term. Block	Pd, Pi AC +12V Term. Block	12V DC Term. Block	24V DC Term. Block	-48V DC Term. Block	
Office Grade/Wiring Closet (CSN14-)										
CSN14*-d, i	X			X						X
Hardened for Factory Floor (CSN14H-)										
CSN14*H-Hd, Hi		X			X		X			X
CSN14*H -12VDC		X					X			X
CSN14*H -24VDC		X						X		X
CSN14*HR -24VDC		X						X		DIN-Rail
CSN14*H -48VDC		X							X	X
Premium Rated for Outdoors (CSN14P-)										
CSN14*P-Pd, Pi			X			X	X			X
CSN14*P -12VDC			X				X			X
CSN14*P 24VDC			X					X		X
CSN14*PR -24VDC			X					X		DIN-Rail
CSN14*P -48VDC			X						X	X

Each power supply is auto-ranging 110-240vac, 50-60Hz, rated at 40 watts at 50°C.

for single mode, add an "S" in place of the asterick () in the chart above; for multi-mode, simply delete the asterick (*).